

Available Options

- HP 10, 20
- Feed Opening 39" X 39"

Model Specifications	20 HP	5" Cylinder	35" Stroke
• Feed opening			25" x 18"
• Bale Chamber			20" x 20" x 35"
• Bale Size expandable			20" x 20" x 43"
• Bale Weight			250 – 300 lbs.
• Machine Weight			7,700 lbs.
• Main Baler Body Frame			SS41
• Cutting Knife Replaceable			Tool Steel Scatter Cutter
• Auto Tier			Hydraulic Actuated Inserter
• Number of Ties			3
• Wire Arrangement			50, 100 lb. spools
• Ram Face Pressure			120 PSI
• Cycle Time (No Load)			6.4 Sec.
• Production (O.C.C.)			2.5 – 3 TPH

Hydraulic System

• Hydraulic System	Regenerative
• Oil Reservoir	130 Gallons 500 Liters
• Hydraulic cooling	Air Cooling
• Hydraulic filtration	Suction Filter
• Hydraulic Pump Brand	DENISON
• Valve Brand	VICKERS

Electrical System (UL)

- PLC MITSUBISHI
- Operator Interface Human Machine Interface
- Main Motor Control STAR/DELTA
- Controller Brand SIEMENS
- UL Standard

After Service System

- Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: steel wire (2.7mmDIA) annealed twice, cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.