

# GB-7575F-1804

## Available Options

- HP 20, 30, 40
- Cylinder 6", 7"
- Feed Opening 39" X 59"

Model Specifications	40 HP	7" Cylinder	63" Stroke
• Feed opening			40" x 28"
• Bale Chamber			30" x 30" x 63"
• Bale Size expandable			30" x 30" x 47" (Adjustable)
• Bale Weight			Up to 1,000 lbs.
• Tension Cylinder			7" Diameter 7" Stroke
• Machine Weight			17,500 lbs.
• Main Baler Body Frame			SS41
• Cutting Knife Replaceable			Tool Steel Scatter Cutter
• Auto Tier			Hydraulic Actuated Inserter
• Number of Ties			4
• Wire Arrangement			50, 100 lb. spools
• Ram Face Pressure			130 PSI
• Tension Force			200 tons
• Tension Type			4-Way Free Floating Clamber
• Cycle Time (No Load)			8.7 Sec.
• Cycles Per Minute			7
• Tie Cycle			19 – 35 Sec.
• Production (O.C.C.)			6 – 8 TPH

## Hydraulic System

- Hydraulic System
- Oil Reservoir
- Hydraulic cooling
- Hydraulic filtration
- Hydraulic Pump Brand
- Valve Brand

Regenerative  
 148 Gallons 560 Liters  
 Air Cooling  
 Suction Filter  
 DENISON  
 VICKERS

### Electrical System (UL)

- PLC
- Operator Interface
- Main Motor Control
- Controller Brand
- UL Standard

MITSUBISHI  
 Human Machine Interface  
 STAR/DELTA  
 SIEMENS

### After Service System

- Complete operations manual. Including installing, operations, maintenance, electrical control diagram, hydraulic circuit diagram, and parts list diagram.

### Remarks

- One year warranty under normal use and maintenance, except for consumables.
- Excludes: Foundation, Electrical wiring outside of machine, hydraulic oil (Shell Tellus R68 or Mobil D.T.E. 26)
- Excludes: steel wire (2.7mmDIA) annealed twice, cyclone and conveying pipes and slat conveyor work, slat conveyor COVER PLATE
- Excluded: Machine installation and test running.